

Suit for
R32

VALUE
VALUE Creates Value

Making Your Job More Enjoyable

N Series Recovery Unit



Only **8.9** ^{VRR12N} **kg**

Light · Fast

Light

- Only 8.9 kg (VRR12N)
- Only 9.2 kg (VRR24N)

Fast and Efficient Recovery

- 2-Cylinder
- 3-row oversized condenser
- Large fan

DC Brushless Motor

- Lighter, faster

Model		VRR12N(single-cylinder)			VRR24N(2-Cylinder)		
Refrigerant		Category III: R-12, R-134a, R-1234YF, R-401C, R-406A, R-500 Category IV: R-22, R-401A, R-401B, R-402B, R-407C, R-407D, R-408A, R-409A, R-502, R-509 Category V : R-143A, R-32, R-402A, R-404A, R-407A, R-407B, R-410A, R-454B, R-507					
Power Supply		220-240V~50/60Hz					
Motor		Brushless DC motor 1HP					
Motor Speed		3000 rpm					
Maximal Current Draw		5 A			7.5 A		
Compressor		Oil-less, Air-cooled, Piston style					
Automatic Safety Shut-Off		38.5bar/3850kPa(558psi)					
Recovery Rate (kg/min)		Categorys III	Categorys IV	Categorys V	Categorys III	Categorys IV	Categorys V
	Vapor	0.22	0.28	0.28	0.44	0.55	0.55
	Liquid	1.76	1.98	2.42	3.30	3.85	3.85
	Push/Pull	5.06	6.16	6.93	8.25	9.35	10.45
Operating Temperature		0°C-40°C					
Dimensions		310×240×245 mm					
Weight		8.9 kg			9.2 kg		